


 Tekla Structural Designer	Project				Job Ref.	
	Structure				Sheet no.	
	Admin Building				Page 1/3	
	Calc. by	Date	Chk'd by	Date	App'd by	Date

SB 1/A.9/5-1/A.9/5.9



St. 1 (1): SB 1/A.9/5-1/A.9/5.9 - 1 (W 30x99 A992-50 (40) [Deformed # 3 @ 8])

Restraints

Source	Distance / Length [ft, in]	LTB Top / Sub -Beam	LTB Top Factor	LTB Btm / Sub -Beam	LTB Btm Factor	Strut Major / Sub-Beam	Strut Major Factor	Strut Minor / Sub-Beam	Strut Minor Factor
support	0"	•		•		•		•	
sub-beam	5' 3"		1.000		1.000		1.000		1.000
member	5' 3"	•						•	
sub-beam	6' 9"		1.000		1.000		1.000		1.000
member	12' 0"	•						•	
sub-beam	6' 9"		1.000		1.000		1.000		1.000
member	18' 9"	•						•	
sub-beam	6' 9"		1.000		1.000		1.000		1.000
member	25' 6"	•						•	
sub-beam	6' 9"		1.000		1.000		1.000		1.000
member	32' 3"	•						•	
sub-beam	6' 1"		1.000		1.000		1.000		1.000
support	38' 4"	•		•		•		•	

Connectors\Layout

Name Diameter As welded height Specified ultimate tensile strength
 AISC 3/4 x 4 3/8 3/4 4 65.00

Distance end 1 [ft, in]	Distance end 2 [ft, in]	Number of connectors in length	Number of connectors in group	Group spacing distance [in]
0"	38' 4"	40	1	11 1/2

Decking

Manufacturer Name Gauge Yield strength
 USD B-LOK 33ksi 30" 1/32 in 33.00 ksi

Slab

Overall depth Effective Width Concrete type Minimum compressive strength, f_c'
 3 15/16 in 10' 1" ft, in Normal 4.00 ksi

Reinforcement

Transverse reinforcement	Reinforcement for crack control or fire requirements				
Type	Area	Yield strength	Type	Area	Yield strength
Deformed # 3 @ 8	0.17 in ² /ft	60.00 ksi	6x6 W1.4xW1.4	0.03 in ² /ft	65.00 ksi

 Tekla Structural Designer	Project						Job Ref.	
	Structure						Sheet no.	
	Admin Building						Page 2/3	
	Calc. by	Date	Chk'd by	Date			App'd by	Date

Static Design Summary

Summary W 30x99 (40 (40))

Design Condition	#	Design Value	Design Capacity	Units	U.R.	Status
Construction Stage	-	-	-	-	-1.000	Not required
Classification	7	Compact	-	-	-	Pass
Vertical Shear	8	119.4	463.3	kip	0.258	Pass
Flexure	8	1271.5	1574.9	kip ft	0.807	Pass
Connector Resistance	7	20	40 (40)		-	Pass
Natural Frequency	14	0.00	-	Hz	-	Not required
Deflection Self weight	14	0.1	-	in	-	-
Deflection Slab	14	0.4	1.9	in	0.230	Pass
Deflection Dead	14	0.6	1.3	in	0.505	Pass
Deflection Post Composite	14	0.6	1.3	in	0.505	Pass
Deflection Total	14	1.2	1.9	in	0.609	Pass

Regional code: United States (ACI/AISC), design code: AISC 360/341 LRFD (2016)

Static Design Calculations

Classification

3D Building Analysis - Critical

7 LRFD₁-1.4D - Critical

Span 1 W 30x99 A992-50 - Critical

Position 18' 9" - Critical

Web class Compact AISC 360 Table B4.1b
 $h / t_w = 51.900$
 h / t_w limit for plastic stress distribution = 90.553

Vertical Shear

3D Building Analysis - Critical

8 LRFD₂-1.2D+1.6L - Critical

Span 1 W 30x99 A992-50 - Critical

Position 0" - Critical

Position of V_{ry} = 0" ft, in
 Required major axis shear strength, V_{ry} = 119.4 kip
 Design shear strength = 463.3 kip AISC 360 G2
 Ratio = 0.258

Pass

Flexure

3D Building Analysis - Critical

8 LRFD₂-1.2D+1.6L - Critical

Span 1 W 30x99 A992-50 - Critical

18' 9" Max Moment Position - Critical

Distance of M along member = 18' 9" ft, in
 Required flexural strength, M_x = 1271.5 kip ft
 Design flexural strength = 1574.9 kip ft
 Ratio = 0.807

Pass

 Tekla Structural Designer	Project				Job Ref.	
	Creech DRP PH2					
	Structure				Sheet no.	
	Admin Building				Page 3/3	
	Calc. by	Date	Chk'd by	Date	App'd by	Date
	Allison Valencia	11/7/2025				

Connector Resistance

3D Building Analysis - Critical

7 LRFD₁-1.4D - Critical

Span 1 W 30x99 A992-50 - Critical

18' 9" Max Moment and UR Position - Critical

Layout and strength of shear connectors

Maximum group spacing, s	=11 1/2 in
Maximum permitted group spacing	=31 1/2 in
Number of shear connectors over full beam length	40
Number of shear connectors to critical point, N _a	20
Degree of shear connection	=0.300
Absolute minimum degree of shear connection	=0.250
Optimum amount of shear connection	=0.500

Partial shear connection

 Pass

Deflection

3D Building Analysis - Critical

14 (Operating) LRFD_{11.1}-1.2D+L+0.15S+E - Critical

Span 1 W 30x99 A992-50 - Critical

Deflection Total - Critical

Short term inertia, I _{qs}	=9359.5 in ⁴
Long term inertia, I _{qL}	=7025.6 in ⁴
Short term inertia @ partial interaction, I _{qs}	=6930.1 in ⁴
Long term inertia @ partial interaction, I _{qL}	=5652.2 in ⁴
Position Total load deflection	=19' 1/4" ft, in
Deflection with full shear connection n, δ	=1.0 in
Deflection of steel beam alone, δ _s	=1.4 in
Minimum degree of shear connection	=29.98 %
Deflection with partial shear connection, δ	=1.2 in
Span over limit	=1.9 in
Design limit	=1.9 in
Utilization Ratio	=0.609

 Pass